Timber Trek Tower 2

Rfmt106

Serial number	Rfmt106
Product line	Robinia Multiplay
Dimensions	436 * 290 cm
Height	≈ 190 cm
FFH	100 cm
In accordance with norm EN	EN1176:17
Age group	5 +
Key user group	5 – 10 years
Inclusive	No
Number of users	8
Platform height	100 cm

Warranty

10 **10-year guarantee** - Coverage includes structural failure of the robinia components and structures.

5 **5-year guarantee -** Structural strength of steel and stainless steel components

2 **2-year guarantee -** Structural failure of high density polyethylene and plastic components

Check the warranty card for more information

Torosplay Ltd.
Bulgaria
8000, Burgas
55 "Kraina" Street
South Industrial Zone

Activities

TOROSPLAY

Options

The Robinia wood can be supplied as untreated raw wood, painted with a brown coloured transparent pigment that maintains the golden wood colour or in a coloured version where selected components are painted in different colours.

Inclined robinia ramp with 5 holding grips attached to each board

Torosplay Ltd.
Bulgaria
8000, Burgas
55 "Kraina" Street
South Industrial Zone

A vertical climbing net that provides a more adventurous climbing experience



Horizontal beam bridge that encourages children to learn the “give way”.



GRP slide with HDPE side panels. Suitable for places with direct sunlight.

Stainless steel slide - The high quality of the materials used and solid welding guarantees high resistance to mechanical damage - 2 mm thick sheet metal, steel pipe fi 33,7 mm, durable linear welding.

Rope handles attached to a specific stainless steel hardware.

TOROSPLAY

The playground equipment consists of a two triangular platforms at a single height. It features a slide, an inclined ramp, and a climbing net. The horizontal robinia beam bridge encourages children to learn the “give way” and to learn balancing and moving while balancing.





Cargo details

On a single pallet: 140*400*160 cm / 475 kgs.



Torosplay Ltd.
Bulgaria
8000, Burgas
55 "Kraina" Street
South Industrial Zone

The hardware is made of stainless steel or galvanized steel to ensure durable connections with a high corrosion resistance. This robust construction guarantees long-lasting performance even in harsh environments.

Design your own:
Wide color pallet to choose colors from
We use only certified EN71 chemical free paints

Robinia boards – 9/14 * 2,5.
Sanded, chamfered R=5mm,
Quality – A,B

Robinia poles 14 – 22 cm in diameter, best possible quality, sanded

16 and 18 mm
PP-Multifilament & split film
Or Braided nylon
Steel core – highest quality

Solid T and X connector ensure the Durability of the nets we produce

Torosplay Ltd.
Bulgaria
8000, Burgas
55 "Kraina" Street
South Industrial Zone

TOROSPLAY

Surfaces according to EN 1176-1:2017

№	Material	Description	min. layer thickness mm	max. fall height mm
1.	concrate			≤ 600
2.	asphalt			≤ 600
3.	topsoil			≤ 1000
4.	turf			≤ 1500
5.	bark	20 - 80 mm grain size borken bark of conifers	200	≤ 2000
			300	≤ 3000
6.	wood chips	5 - 30 mm grain size mechanically broken wood, without bark and leaf components	200	≤ 2000
			300	≤ 3000
7.	sand		200	≤ 2000
			300	≤ 3000
8.	gravel		200	≤ 2000
			300	≤ 3000
9.	other		according to producer	≤ 3000

Installation method Type A: ≈ 1,3 m3 concrete into the ground



Installation method Type B: Anchoring



Torosplay Ltd.
Bulgaria
8000, Burgas
55 "Kraina" Street
South Industrial Zone